

# Table of Contents

|                                        |   |
|----------------------------------------|---|
| <b>RAID</b>                            | 1 |
| <b>1. Membuat RAID 1 SDC &amp; SDD</b> | 1 |
| 1.1 Format Hardisk                     | 1 |
| 1.2 Buat RAID Array                    | 2 |
| 1.3 Mengganti Hardisk RAid             | 3 |
| <b>2. Referensi</b>                    | 4 |



# RAID

Dokumentasi seputar RAID

## 1. Membuat RAID 1 SDC & SDD

Membuat raid array full size dan berikut ini tahapannya

### 1.1 Format Hardisk

```
fdisk /dev/sdc
```

ikuti opsi ini

```
Command (m for help): n
Command action
  e   extended
  p   primary partition (1-4)
p
Partition number (1-4): 1
First cylinder (1-8910, default 1):
Using default value 1
Last cylinder or +size or +sizeM or +sizeK (1-8910, default 8910): (
langsung enter apabila full size )
```

Kemudian tampilkan hasilnya

```
Command (m for help): p
Disk /dev/sdc: 250.1 GB, 250059350016 bytes
255 heads, 63 sectors/track, 30401 cylinders
Units = cylinders of 16065 * 512 = 8225280 bytes
Sector size (logical/physical): 512 bytes / 4096 bytes
I/O size (minimum/optimal): 4096 bytes / 4096 bytes
Disk identifier: 0x000923aa
```

| Device    | Boot | Start | End   | Blocks    | Id | System |
|-----------|------|-------|-------|-----------|----|--------|
| /dev/sdc1 |      | 1     | 30401 | 244196001 | 83 | Linux  |

Aktifkan partisi sebagai Raid Auto Detect

```
Command (m for help): t
Selected partition 1
Hex code (type L to list codes): fd
Changed system type of partition 1 to fd (Linux raid autodetect)
```

Command (m for help): p

Disk /dev/sdc: 250.1 GB, 250059350016 bytes  
 255 heads, 63 sectors/track, 30401 cylinders  
 Units = cylinders of 16065 \* 512 = 8225280 bytes  
 Sector size (logical/physical): 512 bytes / 4096 bytes  
 I/O size (minimum/optimal): 4096 bytes / 4096 bytes  
 Disk identifier: 0x000923aa

| Device    | Boot | Start | End   | Blocks    | Id | System     |
|-----------|------|-------|-------|-----------|----|------------|
| /dev/sdc1 |      | 1     | 30401 | 244196001 | fd | Linux raid |

autodetect  
 Partition 1 does not start on physical sector boundary.

Lakukan hal yang sama seperti diatas pada SDD

## 1.2 Buat RAID Array

Lihat dulu partisi array yang ada pastikan jangan sampai bentrok

```
cat /proc/mdstat
```

hasilnya

```
Personalities : [raid1]
md1 : active raid1 sda3[0] sdb3[1]
      306880 blocks super 1.1 [2/2] [UU]

md0 : active raid1 sda1[0] sdb1[1]
      614336 blocks super 1.0 [2/2] [UU]

md127 : active (auto-read-only) raid1 sda4[0] sdb4[1]
      2826812224 blocks super 1.1 [2/2] [UU]
      resync=PENDING
      bitmap: 22/22 pages [88KB], 65536KB chunk

md2 : active raid1 sdb2[1] sda2[0]
      102334336 blocks super 1.1 [2/2] [UU]
      bitmap: 1/1 pages [4KB], 65536KB chunk
```

anda bisa menggunakan misalnya md3 caranya

```
mdadm --create /dev/md3 --level=1 --raid-devices=2 /dev/sdc1 /dev/sdd1
```

dan pantau perubahannya

```
watch cat /proc/mdstat
```

dan hasilnya

```
Personalities : [raid1]
md3 : active raid1 sdd1[1] sdc1[0]
      244064896 blocks super 1.2 [2/2] [UU]
      [=====>.....]    resync = 34.6% (84689728/244064896)
finish=19.7min speed=134492K/sec
      bitmap: 2/2 pages [8KB], 65536KB chunk

md1 : active raid1 sda3[0] sdb3[1]
      306880 blocks super 1.1 [2/2] [UU]

md0 : active raid1 sda1[0] sdb1[1]
      614336 blocks super 1.0 [2/2] [UU]

md127 : active (auto-read-only) raid1 sda4[0] sdb4[1]
      2826812224 blocks super 1.1 [2/2] [UU]
      resync=PENDING
      bitmap: 22/22 pages [88KB], 65536KB chunk

md2 : active raid1 sdb2[1] sda2[0]
      102334336 blocks super 1.1 [2/2] [UU]
      bitmap: 0/1 pages [0KB], 65536KB chunk
```

### 1.3 Mengganti Hardisk RAid

Apabila anda sudah menambahkan hardisk baru /dev/sdb maka cara menambahkan hdd tsb ke raid adalah sbb

Anda tidak perlu melakukan partisi satu per satu, untuk membuat partisi /dev/sdb sama dengan partisi /dev/sda anda bisa menggunakan perintah sfdisk berikut ini

```
sfdisk -d /dev/sda | sfdisk /dev/sdb
```

Selanjutnya lihat hasilnya dengan

```
lsblk
```

setelah anda yakin partisinya sama, selanjutnya tambahkan ke raid, misalnya

```
mdadm --manage /dev/md0 --add /dev/sdb1
```

lakukan sesuai dengan partisi yang ada dalam raid.

## 2. Referensi

1. <http://www.cyberciti.biz/faq/centos-redhat-rhel-linux-setup-create-raid1/>

From:

<https://www.pusathosting.com/kb/> - **PusatHosting Wiki**

Permanent link:

<https://www.pusathosting.com/kb/linux/raid?rev=1459783403>

Last update: **2016/04/04 11:23**

